

AROCS 2640 6X4



SANY HEAVY INDUSTRY CO. LTD

Mercedes-Benz
Trucks you can trust



Orderdata (Order 1350613082)

A1D	Front axle 8.0 t	L0A	Illumination regulation, in acc. with UN-R 48.06
A1X	Straight front axle, increased ground clearance	L1C	LED daytime running lamps
A2F	Rear axle, crown wheel 233, planetary, 13.4 t	L1W	LED turn signals in light signature
A5Y	Axle ratio i = 4.333	L2H	Side marker lamps, flashing
B1B	Electronic braking system with ABS and ASR	M0C	Bottom shell to prevent swirling-up of dust
B1F	Heating, electronic air-processing unit	M0Q	Noise regulation acc. to UN-R 51.03, phase 2
B1H	Electr. compressed air supply and control, centre	M2Q	Eng. OM470, inline 6, 10.7 l, 290kW (394hp), 1900 Nm
B1Z	ABS, disengageable	M4X	Engine version Euro VI, E
B2A	Disc brakes on front and rear axle	M5A	2. Engine generation OM470
B2X	Parking brake, electronic	M5V	High Performance Engine Brake
B4A	Condensation monitoring, for compressed air sys.	M6L	Air compressor, 2-cylinder
B4L	All compressed air tanks, aluminium	M7I	Insect screen in front of cooling system
CLW	Steering oil cooling	M8A	Air intake from front
C0T	Frame overhang 1650 mm	M8Y	Fuel pre-filter, chassis-mounted, additional
C2N	Wheelbase 4500 mm	M9V	Deletion, guard plate, bumper
C5P	Bolted frame	N6P	Prov. for PTO, via external transfer case
C6C	Steering, single-circuit	N6Z	Transmission oil cooling
C6I	Power steering pump, controlled	O0A	Coolant service interval, long for non-SWR
C6Q	Stabiliser, front axle	O0T	TruckLive
C6Y	Stabiliser, under frame, rear axle	O1A	Fuel pre-filter, 1st position
C7I	Battery carrier cover, lockable	O1T	Interior colour greige/anthracite
C7K	Battery carrier, batteries stacked	O1Z	Steering, indirect
C7Q	Free space for crane outrigger feet	O2N	Starter Melco 95P65
C8F	Wing, for chassis transit	O2X	Optimised cab separation point, supply
C9S	Deletion mounting parts, on frame	O3K	Active Safety
C9Y	Deletion, rear underride guard (ECE)	P0Q	Cover, for wheel arch and engine
D0S	Compressed-air connection, in cab	Q1N	Front spring, 8.0 t, 3-leaf
D1B	Driver's suspension seat, standard	Q2Q	Rear spring, 2 x 10,0 t, hard
D1N	Fold-up co-driver's seat	Q8W	End crossmember, 100 mm indented
D2N	Driver's seat backrest, release mechanism	R0L	Tyres, customer request, FA
D2Y	Seat belt monitor	R0N	Tyres, customer request, RA
D3X	Seat cover, flat-weave fabric	R0O	Tyres, customer request, 2nd RA/twinty.trail.axle
D5Y	Rubber mats, driver's and co-driver's side	R0Z	Wheel-nut cap
D6F	Air conditioning system	R1N	15-degree tapered rims, 8.25 x 22.5
D6I	Residual engine heat utilisation	R1R	15-degree tapered rims, 9.00 x 22.5, front axle
D6Z	Construction-site filter	S1H	Lane Keeping Assist
D7G	Stowage compartment lid, driver and co-driver side	S1L	Attention Assist
D7P	Tray, low, on engine tunnel	S1O	Traffic Sign Assist
D8A	Roof hatch/vent, roof	S1Y	Tyre pressure monitor
E0D	Battery sensor, Hella	S2D	Active Brake Assist 6
E0F	Batteries from company Exide	S2H	Active Sideguard Assist 2
E1B	Batteries 2 x 12 V/170 Ah, low-maintenance	S2L	Frontguard Assist
E1N	Alternator 28 V/100 A	S4A	Pre-installation for alcohol test on start-up lock
E2J	Automatic cutouts	S5A	Speed limiter, 90 km/h (56 mph), ECE
E3L	Socket, 24 V/15 A, co-driver footwell	S5Z	Cruise control

Orderdata (Order 1350613082)

E3W	PSM, 2nd generation	S8A	First aid kit
E5G	Battery disconnect switch outside, on frame	S8B	Fire extinguisher, 2 kg
E6Z	Reversing buzzer	S8C	Hazard warning triangle
E9E	Provision, ADR, without chassis shielding	S8D	Warning lamp
F0E	M-cab, low roof, 2.30 m, tunnel 320 mm	S8E	Reflective safety jacket
F0G	Side module, N3G vehicle	U0Q	Control code, HDEP Fuel Efficiency Package - FE1
F0Y	Mirror cover, construction vehicle	U1W	AdBlue lines, water-heated
F1Q	M-cab	U2G	Exhaust box
F2C	Floor variant, tunnel 320 mm	U2M	Control code, ASAM
F2G	Cab width 2.30 m	U2T	Control code, exhaust box, rear outlet
F2M	Cab, 420 mm attachment height	U2U	Control code, catalytic converter kit 1
F2Y	ClassicSpace Low Roof	U3D	Control code, CAN star points, classic
F3A	Cab mountings, standard, steel-sprung	U3F	Control code, global AdBlue sensor (GMS DEF)
F3W	Cab tilting mechanism, mechanical-hydraulic	U3S	3rd-generation electronics architecture
F4H	Cab rear wall, without window	U3W	ICUC hardware Gen6.
F4X	Stowage compartment exterior flap, left	V0Q	Vehicle version in acc. w. GSR, phase B
F5Y	A-pillar trim	V0T	Vehicle class N3G, off-road vehicle
F6D	Windscreen, tinted, with filter band	V0U	Overhang angle, front, minimum 25 degrees
F6I	Front mirror, heated	V0X	Ground clearance under front axle, minimum 250 mm
F7B	Bumper, with steel corners	V0Y	Ground clearance under rear axle, minimum 250 mm
F7D	Bumper centre section w. towing eyes, coupling	V0Z jaw	Ground clearance between axles, minimum 300 mm
F7Y	Cab entrance, left/right, movable	V1B	Arocs
F8B	2 remote control keys	V1W	Standard
F8E	Locking system, with central locking	V2J	Arocs model generation 5
G0K	Drive program, economy/power	V5A	Specification, France
G0R	Transmission support arms, optimised for removal	V8A	Chassis number FIN
G0T	Predictive Powertrain Control	V9F	Technical changes model year April
G2C	Transmission G 230-12/11.7-0.78	W4E	Weight variant 28.0 t (8.0/10.0/10.0)
G5A	Single-disc clutch	X1B	Instrument/labels/documentation, French
G5G	Mercedes PowerShift 3	X2E	Model plate, EU
G5L	PowerShift Advanced	X2T	Maintenance Documentation
G5Y	Tachograph calibration, digital, ex factory	X3Z	Powertrain warranty as per T and Cs 3yrs/250,000km
I1F	Tyres, tubeless, size 11 R 22.5, rear axle	X4K	Literature in English, additional
I2E	Tyres tubeless, 315/70 R 22.5, fr./lead./trl. axle	Y1F	Assignment of cab paintwork, top coat line 1
I4I	Wheel arrangement 6x4	Y4J	2 wheel chocks
I5F	26.0-tonner	Y4Z	Compressed-air gun, with hose
I6A	Rigid chassis	Z1H	EBS, Wabco
I6I	Vehicle production plant Wörth	Z1Y	EAPU equipment, item 2
I6K	Heavy-duty model series, new generation from 18 t	Z2E	Battery circuit breaker equipment, item 5
I6M	Heavy-duty vehicles from 18 t, off-road	Z3A	Switch module 1, type A
I6W	Leaf suspension, rear axle	Z3F	Switch module 7
J1H	Instrument cluster, 12.7 cm	Z3H	Side marker lights, 1st pair

Orderdata (Order 1350613082)

J1M	Dig. tachograph, 2nd gen., version 2, ADR	Z3J	Side marker lights, 3rd pair
J1S	Tachograph manufacturer VDO	Z3K	Side marker lights, 4th pair
J2H	Multimedia Radio Touch	Z3Z	Export code
J2I	Standard loudspeaker	Z4O	Tank cross-section, narrow
J3U	Requirement: FleetBoard Manager app	Z4Q	Tank cross-section, low
J6A	Classic Cockpit	Z5D	OM 470
J6W	Reversing camera, towing vehicle end	Z5G	Fan position, on crankshaft
J7A	Truck Data Center 8	Z5I	Fan ratio, 1:1.0
J7V	Driving assistance map, Europe region	Z5P	Clutch supplier F&S
J8U	Pre-installation for Truck Data Center 8	Z5V	Starter with M10, HDEP
J9D	Provision for fitting toll tracking	Z5X	Left-hand drive
K0T	Main tank, left	Z5Y	Vehicle, for right-side traffic
K3V	AdBlue tank, 60 l, left	Z8E	Plausibility control code (internal)
K5A	Tank, 290 l, left, 650 x 565 x 950 mm, steel	Z8M	CTT vehicle, conversion at Molsheim plant
K5M	Tanks, lockable	Z8P	CTT vehicle, conversion on assembly line
K5Q	Fuel screen, tank filler neck	Z8U	CTT vehicle
K5S	Protective cap for AdBlue metering system	Z9A	Constructability request order, special control
K8D	Exhaust sys.,tailpipe to right/outwards,horizontal		

SP-REQ. no.	Description
W/JC7K	Battery carrier, batteries stacked
W/JC7Q	Free space for crane outrigger feet
1/AHM04-40	Mercedes-Benz Molsheim
1/AJCUF	Offer: Frame overhang 1550 mm
1/AJKVA	Offer: tank moved to measure 2425 mm
1/AJK1D	Offer: Tank, 330 l, left, 650 x 565 x 1050 mm, aluminium
1/AJZAH	Offer: "Sany" customer vehicle
1/AJZNXB015C	Offer: Modification in accordance with plan number "X"
1/AJZSXB015D	Offer: Modification in accordance with spezifikation number "X"
1/A23060W380	
1/JBCS	Overflow valve for auxiliary consumers
1/JBWC	2 Move air tank to frame/overhang
1/JCAJ	1st crossmember behind transmission at 2050mm
1/JCMX	Shortening of frame overhang
1/JZNX	Modification in accordance with plan number "X"
1/JZSX	Modification in accordance with spezifikation number "X"
1/JZVF	Free space for installation of hydraulic pump with propshaft